

# 861 Receiving Advice/Acceptance Certificate

Functional Group ID=**RC**

## Introduction:

This Draft Standard for Trial Use contains the format and establishes the data contents of the Receiving Advice/Acceptance Certificate Transaction Set (861) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business and industry practice relative to the notification of receipt or formal acceptance of goods and services.

## Notes:

- 1. Receiving activities use this transaction set to report the acceptance of material at destination.*
- 2. Use a single occurrence of this transaction set to report and cancel destination acceptance information, even when the originating activity is not in receipt of an acceptance alert.*
- 3. Use one occurrence of this transaction set to transmit a single or multiple original and cancellation acceptance reports.*
- 4. DoD, Federal and Civil Agency users operating under the Defense Logistics Management Systems (DLMS) must reference the Unit of Issue and Purchase Unit Conversion Table available at URL: <http://www.dla.mil/j-6/dlms>.*

## Heading:

Page No.	Pos. No.	Seg. ID	Name	Req. Des.	Max.Use	Loop Repeat	Notes and Comments
4	010	ST	Transaction Set Header	M	1		
5	020	BRA	Beginning Segment for Receiving Advice or Acceptance Certificate	M	1		n1
Not Used	040	CUR	Currency	O	1		
7	050	REF	Reference Identification	O	>1		
9	060	PER	Administrative Communications Contact	O	3		
11	070	DTM	Date/Time Reference	M	10		
13	080	PRF	Purchase Order Reference	O	25		
Not Used	090	TD1	Carrier Details (Quantity and Weight)	O	2		
Not Used	100	TD5	Carrier Details (Routing Sequence/Transit Time)	O	12		
Not Used	110	TD3	Carrier Details (Equipment)	O	12		
Not Used	120	TD4	Carrier Details (Special Handling, or Hazardous Materials, or Both)	O	5		
Not Used	125	MEA	Measurements	O	40		
LOOP ID - N1						200	

15	130	N1	Name	O	1
Not Used	140	N2	Additional Name Information	O	2
Not Used	150	N3	Address Information	O	2
Not Used	160	N4	Geographic Location	O	1
Not Used	170	REF	Reference Identification	O	100
Not Used	180	PER	Administrative Communications Contact	O	3
Not Used	190	FOB	F.O.B. Related Instructions	O	1
LOOP ID - LM					10
17	200	LM	Code Source Information	O	1
18	210	LQ	Industry Code	M	100

***Detail:***

Page No.	Pos. No.	Seg. ID	Name	Req. Des.	Max.Use	Loop Repeat	Notes and Comments
LOOP ID - RCD							200000
19	010	RCD	Receiving Conditions	O	1		
28	020	SN1	Item Detail (Shipment)	O	1		
Not Used	030	CUR	Currency	O	1		
Not Used	040	LIN	Item Identification	O	100		
Not Used	050	PID	Product/Item Description	O	1000		
Not Used	060	PO4	Item Physical Details	O	100		
30	070	REF	Reference Identification	O	12		
Not Used	080	PER	Administrative Communications Contact	O	3		
33	090	DTM	Date/Time Reference	O	10		
35	100	PRF	Purchase Order Reference	O	25		
Not Used	110	MEA	Measurements	O	>1		
Not Used	120	FOB	F.O.B. Related Instructions	O	1		
Not Used	130	TD1	Carrier Details (Quantity and Weight)	O	20		
Not Used	140	TD5	Carrier Details (Routing Sequence/Transit Time)	O	12		
Not Used	150	TD3	Carrier Details (Equipment)	O	12		
Not Used	160	TD4	Carrier Details (Special Handling, or Hazardous Materials, or Both)	O	5		
Not Used	170	SAC	Service, Promotion, Allowance, or Charge Information	O	10		
Not Used	180	MAN	Marks and Numbers	O	>1		
LOOP ID - LM							10
37	185	LM	Code Source Information	O	1		
38	186	LQ	Industry Code	M	100		
LOOP ID - SLN							100
39	190	SLN	Subline Item Detail	O	1		
44	200	PID	Product/Item Description	O	1000		
Not Used	203	NM1	Individual or Organizational Name	O	1		
LOOP ID - LM							10
46	205	LM	Code Source Information	O	1		
47	206	LQ	Industry Code	M	100		
LOOP ID - N1							200

Not Used	210	N1	Name	O	1	
Not Used	220	N2	Additional Name Information	O	2	
Not Used	230	N3	Address Information	O	2	
Not Used	240	N4	Geographic Location	O	1	
Not Used	250	REF	Reference Identification	O	100	
Not Used	260	PER	Administrative Communications Contact	O	3	
Not Used	270	FOB	F.O.B. Related Instructions	O	1	

***Summary:***

<b>Page No.</b>	<b>Pos. No.</b>	<b>Seg. ID</b>	<b>Name</b>	<b>Req. Des.</b>	<b>Max.Use</b>	<b>Loop Repeat</b>	<b>Notes and Comments</b>
Not Used	010	CTT	Transaction Totals	O	1		n2
48	020	SE	Transaction Set Trailer	M	1		

***Transaction Set Notes***

1. This transaction set is a Receiving Advice unless BRA04 contains a value of "8". When BRA04 contains a value of "8", the transaction set is an Acceptance Certificate and the units received is the units accepted.
2. The number of line items (CTT01) is the accumulation of the number of RCD segments. If used, hash total (CTT02) is the sum of the value of quantities received (RCD02) for each RCD segment.

**Segment:** **ST** Transaction Set Header  
**Position:** 010  
**Loop:**  
**Level:** Heading  
**Usage:** Mandatory  
**Max Use:** 1  
**Purpose:** To indicate the start of a transaction set and to assign a control number  
**Syntax Notes:**  
**Semantic Notes:** 1 The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).  
**Comments:**

#### Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	ST01	143	Transaction Set Identifier Code	M ID 3/3
			Code uniquely identifying a Transaction Set	
			861 Receiving Advice/Acceptance Certificate	
M	ST02	329	Transaction Set Control Number	M AN 4/9
			Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	
			<i>A unique number assigned by the originator of the transaction set, or the originator's application program.</i>	

**Segment:** **BRA** Beginning Segment for Receiving Advice or Acceptance Certificate

**Position:** 020

**Loop:**

**Level:** Heading

**Usage:** Mandatory

**Max Use:** 1

**Purpose:** To indicate the beginning of a Receiving Advice or Acceptance Certificate Transaction Set and transmit an identifying number, date, and time

**Syntax Notes:**

**Semantic Notes:**

- 1 BRA02 is the date that the receiving advice transaction set is created.
- 2 BRA05 is the time that the receiving advice transaction set is created.

**Comments:**

#### Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>		
M	BRA01	127	<b>Reference Identification</b>	M AN 1/30
			Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	
			<i>Use "Z" for this data element. This "Z" entry satisfies the X12 usage requirements; the receiving application software shall not process it.</i>	
M	BRA02	373	<b>Date</b>	M DT 8/8
			Date expressed as CCYYMMDD	
			<i>Express the originating activity's date in UTC (Universal Time Coordinate).</i>	
M	BRA03	353	<b>Transaction Set Purpose Code</b>	M ID 2/2
			Code identifying purpose of transaction set	
			00 Original	
			<i>Use regardless of the type of acceptance report, unless a cancellation or correction.</i>	
			01 Cancellation	
			CO Corrected	
M	BRA04	962	<b>Receiving Advice or Acceptance Certificate Type Code</b>	M ID 1/1
			Code specifying type of receiving advice	
			<i>Use when the transaction set contains one or more reports, regardless of the type of the acceptance report.</i>	
			8 Acceptance Certificate	
			9 Authorized Representative in Receipt of an Acceptance Alert	
			An acknowledgment that acceptance has taken place (at destination) by an authorized (government) representative who had been previously alerted to the	

fact that there is a shipment inbound for which acceptance at destination will be required

***Use to identify a party in receipt of an acceptance alert.***

A

Authorized Representative Not in Receipt of an Acceptance Alert

An acknowledgment that acceptance has taken place (at destination) by an authorized (government) representative who had not been previously alerted to the fact that there is a shipment inbound for which acceptance at destination will be required

***Use to identify a party not in receipt of an acceptance alert.***

<b>Must Use</b>	<b>BRA05</b>	<b>337</b>	<b>Time</b>	<b>O TM 4/8</b>
			Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	
			<b><i>1. Express the originating activity's time in UTC.</i></b>	
			<b><i>2. Express time in a four-position (HHMM) format.</i></b>	
<b>Not Used</b>	<b>BRA06</b>	<b>412</b>	<b>Receiving Condition Code</b>	<b>O ID 2/2</b>
			Code designating physical condition or status of units received in a specific shipment	
<b>Not Used</b>	<b>BRA07</b>	<b>306</b>	<b>Action Code</b>	<b>O ID 1/2</b>
			Code indicating type of action	

<b>Segment:</b>	<b>REF</b> Reference Identification
<b>Position:</b>	050
<b>Loop:</b>	
<b>Level:</b>	Heading
<b>Usage:</b>	Optional
<b>Max Use:</b>	>1
<b>Purpose:</b>	To specify identifying information
<b>Syntax Notes:</b>	<ol style="list-style-type: none"> <li>1 At least one of REF02 or REF03 is required.</li> <li>2 If either C04003 or C04004 is present, then the other is required.</li> <li>3 If either C04005 or C04006 is present, then the other is required.</li> </ol>
<b>Semantic Notes:</b>	<ol style="list-style-type: none"> <li>1 REF04 contains data relating to the value cited in REF02.</li> </ol>
<b>Comments:</b>	
<b>Notes:</b>	<i>Use this 1/REF/050 segment to identify reference numbers that apply to all of the line items. If the reference numbers vary by line item, use the 2/REF/070 segment.</i>

## Data Element Summary

Ref.	Data	Name	Attributes
Des.	Element		
M	REF01	128 Reference Identification Qualifier	M ID 2/3
		Code qualifying the Reference Identification	
		55	Sequence Number
			<i>Use, if applicable, to identify the suffix letter associated with a replacement shipment (e.g., when transmitting the letter A to indicate the first replacement shipment).</i>
		AT	Appropriation Number
			<i>Use to indicate a long line of accounting. Cite the line of accounting in REF03.</i>
		AX	Government Accounting Class Reference Number (ACRN)
		FS	Final Sequence Number
			<i>Use, if applicable, to identify the final shipment suffix Z.</i>
		FU	Fund Code
			Defense Fuel Supply Center to bill back fuel purchases to the appropriate service or agency account fund
		IL	Internal Order Number
			<i>Use to indicate a Communication Service Authorization (CSA) number.</i>
		SI	Shipper's Identifying Number for Shipment (SID)
			A unique number (to the shipper) assigned by the shipper to identify the shipment

			<i>Use to identify the shipment number.</i>	
			TN	Transaction Reference Number
			<i>Use to identify the transaction number associated with the original requisition.</i>	
<b>Must Use</b>	<b>REF02</b>	<b>127</b>	<b>Reference Identification</b>	<b>X AN 1/30</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier
	<b>REF03</b>	<b>352</b>	<b>Description</b>	<b>X AN 1/80</b> A free-form description to clarify the related data elements and their content
<b>Not Used</b>	<b>REF04</b>	<b>C040</b>	<b>Reference Identifier</b>	<b>O</b> To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier
<b>Not Used</b>	<b>C04001</b>	<b>128</b>	<b>Reference Identification Qualifier</b>	<b>M ID 2/3</b> Code qualifying the Reference Identification
<b>Not Used</b>	<b>C04002</b>	<b>127</b>	<b>Reference Identification</b>	<b>M AN 1/30</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier
<b>Not Used</b>	<b>C04003</b>	<b>128</b>	<b>Reference Identification Qualifier</b>	<b>X ID 2/3</b> Code qualifying the Reference Identification
<b>Not Used</b>	<b>C04004</b>	<b>127</b>	<b>Reference Identification</b>	<b>X AN 1/30</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier
<b>Not Used</b>	<b>C04005</b>	<b>128</b>	<b>Reference Identification Qualifier</b>	<b>X ID 2/3</b> Code qualifying the Reference Identification
<b>Not Used</b>	<b>C04006</b>	<b>127</b>	<b>Reference Identification</b>	<b>X AN 1/30</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier



**Segment:** **PER** Administrative Communications Contact  
**Position:** 060  
**Loop:**  
**Level:** Heading  
**Usage:** Optional  
**Max Use:** 3  
**Purpose:** To identify a person or office to whom administrative communications should be directed

**Syntax Notes:**

- 1 If either PER03 or PER04 is present, then the other is required.
- 2 If either PER05 or PER06 is present, then the other is required.
- 3 If either PER07 or PER08 is present, then the other is required.

**Semantic Notes:****Comments:**

**Notes:** *Use to identify a POC.*

**Data Element Summary**

Ref.	Data		
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	PER01	366 Contact Function Code	M ID 2/2
		Code identifying the major duty or responsibility of the person or group named	
		IC Information Contact	
	PER02	93 Name	O AN 1/60
		Free-form name	
		<i>Use to identify the name of a point of contact. Last name, followed by first name, is preferred. If the name is longer than 60 characters, use initials. PER09 may be used to cite the title of the individual.</i>	
	PER03	365 Communication Number Qualifier	X ID 2/2
		Code identifying the type of communication number	
		AU Defense Switched Network	
		Department of Defense telecommunications system and successor of the Automatic Voice Network (AUTOVON)	
		EM Electronic Mail	
		FX Facsimile	
		TE Telephone	
	PER04	364 Communication Number	X AN 1/80
		Complete communications number including country or area code when applicable	
		<i>When transmitting a telephone or fax number, the number shall be transmitted with no extraneous characters. Include the county code and area code. If an extension applies to the number, concatenate the letter "X" plus the extension at the end of the number.</i>	
	PER05	365 Communication Number Qualifier	X ID 2/2

		Code identifying the type of communication number	
		AU	Defense Switched Network
			Department of Defense telecommunications system and successor of the Automatic Voice Network (AUTOVON)
		EM	Electronic Mail
		FX	Facsimile
		TE	Telephone
<b>PER06</b>	<b>364</b>	<b>Communication Number</b>	<b>X AN 1/80</b>
		Complete communications number including country or area code when applicable	
<b>PER07</b>	<b>365</b>	<b>Communication Number Qualifier</b>	<b>X ID 2/2</b>
		Code identifying the type of communication number	
		AU	Defense Switched Network
			Department of Defense telecommunications system and successor of the Automatic Voice Network (AUTOVON)
		EM	Electronic Mail
		FX	Facsimile
		TE	Telephone
<b>PER08</b>	<b>364</b>	<b>Communication Number</b>	<b>X AN 1/80</b>
		Complete communications number including country or area code when applicable	
<b>PER09</b>	<b>443</b>	<b>Contact Inquiry Reference</b>	<b>O AN 1/20</b>
		Additional reference number or description to clarify a contact number	
		<i>Use, if necessary, to provide the title of the party cited in PER02.</i>	

**Segment: DTM Date/Time Reference****Position:** 070**Loop:****Level:** Heading**Usage:** Mandatory**Max Use:** 10**Purpose:** To specify pertinent dates and times

- Syntax Notes:**
- 1 At least one of DTM02 DTM03 or DTM05 is required.
  - 2 If DTM04 is present, then DTM03 is required.
  - 3 If either DTM05 or DTM06 is present, then the other is required.

**Semantic Notes:****Comments:**

**Notes:** *Use this 1/DTM/070 segment to identify dates that apply to all of the line items.  
When the dates vary by line item, use the 2/DTM/090 segment.*

**Data Element Summary**

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	DTM01	374	Date/Time Qualifier	M ID 3/3
Code specifying type of date or time, or both date and time				
<i>Use only one code.</i>				
		018	Available	
<i>Use to indicate the material was offered for delivery.</i>				
		035	Delivered	
<i>Use to indicate the material was delivered.</i>				
		050	Received	
		144	Estimated Acceptance	
<i>Use to indicate the material has an estimated acceptance date. Use in interim reports when LQ01 cites code 10 and LQ02 cites code D.</i>				
		201	Acceptance	
<i>Use to indicate the material was accepted.</i>				
Must Use	DTM02	373	Date	X DT 8/8
Date expressed as CCYYMMDD				
Not Used	DTM03	337	Time	X TM 4/8
Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)				
Not Used	DTM04	623	Time Code	O ID 2/2
Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an				

indication in hours in relation to Universal Time Coordinate (UTC) time;  
since + is a restricted character, + and - are substituted by P and M in the  
codes that follow

**DTM05      1250      Date Time Period Format Qualifier      X      ID 2/3**

Code indicating the date format, time format, or date and time format

YY

Last Two Digits of Year Expressed in Format CCYY

The year in the century (00 to 99)

*Use in conjunction with DTM01 code 050 to  
indicate the FY obligated date.*

**DTM06      1251      Date Time Period      X      AN 1/35**

Expression of a date, a time, or range of dates, times or dates and times

*Enter the fiscal year in YY format.*

**Segment:** **PRF** Purchase Order Reference  
**Position:** 080  
**Loop:**  
**Level:** Heading  
**Usage:** Optional  
**Max Use:** 25  
**Purpose:** To provide reference to a specific purchase order  
**Syntax Notes:**  
**Semantic Notes:** 1 PRF04 is the date assigned by the purchaser to purchase order.  
**Comments:**

**Notes:** *Use this 1/PRF/080 to indicate contract information when the same contract number or Supplemental Procurement Instrument Identification Number (SPIIN) applies to all of the line items. Use the 2/PRF/100 segment when the contract information varies by line item.*

#### Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	PRF01	324	Purchase Order Number	M AN 1/22
			Identifying number for Purchase Order assigned by the orderer/purchaser	
			<i>Enter the purchase order number, contract number (including Federal Supply Schedules, General Services Administration Schedules and all other basic contracts), Blanket Purchase Agreement number, Grant, Lease or Agreement number. This is always the Procurement Instrument identification Number for the Department of Defense or the equivalent expression for Civilian Agencies. This is never the number of a delivery order, call or release against a basic award instrument. That number is carried in PRF02. This number shall be transmitted without dashes.</i>	
	PRF02	328	Release Number	O AN 1/30
			Number identifying a release against a Purchase Order previously placed by the parties involved in the transaction	
			<i>Enter the number of a release, call or delivery order against a basic award instrument. This is always the Supplemental Procurement Instrument Identification Number for the Department of Defense or the equivalent expression for Civilian Agencies. This number shall be transmitted without dashes.</i>	
Not Used	PRF03	327	Change Order Sequence Number	O AN 1/8
			Number assigned by the orderer identifying a specific change or revision to a previously transmitted transaction set	
Not Used	PRF04	373	Date	O DT 8/8
			Date expressed as CCYYMMDD	
Not Used	PRF05	350	Assigned Identification	O AN 1/20
			Alphanumeric characters assigned for differentiation within a transaction set	

	<b>PRF06</b>	<b>367</b>	<b>Contract Number</b> Contract number <i>Use to identify the Small Business Administration (SBA) contract number for an 8a set-aside. The SBA office issuing this contract is cited in 1/N1/130 segment by use of code C9 in N101.</i>	<b>O AN 1/30</b>
<b>Not Used</b>	<b>PRF07</b>	<b>92</b>	<b>Purchase Order Type Code</b> Code specifying the type of Purchase Order	<b>O ID 2/2</b>

<b>Segment:</b>	<b>N1</b> Name
<b>Position:</b>	130
<b>Loop:</b>	N1 Optional (Must Use)
<b>Level:</b>	Heading
<b>Usage:</b>	Optional (Must Use)
<b>Max Use:</b>	1
<b>Purpose:</b>	To identify a party by type of organization, name, and code
<b>Syntax Notes:</b>	<b>1</b> At least one of N102 or N103 is required. <b>2</b> If either N103 or N104 is present, then the other is required.
<b>Semantic Notes:</b>	
<b>Comments:</b>	<b>1</b> This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party. <b>2</b> N105 and N106 further define the type of entity in N101.
<b>Notes:</b>	<i>Use in all transactions. Use the 1/N1/130 loop to identify the ship-to address originating this transaction set.</i>

#### Data Element Summary

Ref.	Data	
<u>Des.</u>	<u>Element</u>	<u>Name</u>
M	N101	98 Entity Identifier Code
		Code identifying an organizational entity, a physical location, property or an individual
		1Q Military Facility
		<i>Use to indicate the expense center.</i>
		C9 Contract Holder
		<i>Use to indicate the Small Business Administration (SBA) office.</i>
		CJ Automated Data Processing (ADP) Point
		A qualifier for an address of a location providing ADP support to an entity that is the intended recipient of a transmission, but that entity does not have its own organic capability to receive the transmission directly, relying instead on the support provided by the ADP point
		<i>Use to indicate internal routing of an incoming transaction.</i>
		SE Selling Party
		<i>Use to indicate the contractor.</i>
		ST Ship To
		<i>Use to identify the ship-to address originating the transaction set.</i>
		Z4 Owning Inventory Control Point
		An inventory control organization responsible for

			management of a particular item	
<b>Not Used</b>	<b>N102</b>	<b>93</b>	<b>Name</b>	<b>X AN 1/60</b>
			Free-form name	
<b>Must Use</b>	<b>N103</b>	<b>66</b>	<b>Identification Code Qualifier</b>	<b>X ID 1/2</b>
			Code designating the system/method of code structure used for Identification Code (67)	
		1	D-U-N-S Number, Dun & Bradstreet	
		9	D-U-N-S+4, D-U-N-S Number with Four Character Suffix	
		10	Department of Defense Activity Address Code (DODAAC)	
		33	Commercial and Government Entity (CAGE)	
		M4	Department of Defense Routing Identifier Code (RIC)	
			An integral and predetermined participant in an established logistical system performing general logistic control, distribution, and storage functions	
<b>Must Use</b>	<b>N104</b>	<b>67</b>	<b>Identification Code</b>	<b>X AN 2/80</b>
			Code identifying a party or other code	
<b>Not Used</b>	<b>N105</b>	<b>706</b>	<b>Entity Relationship Code</b>	<b>O ID 2/2</b>
			Code describing entity relationship	
<b>Must Use</b>	<b>N106</b>	<b>98</b>	<b>Entity Identifier Code</b>	<b>O ID 2/3</b>
			Code identifying an organizational entity, a physical location, property or an individual	
			<b><i>Must use codes FR and TO in conjunction with the appropriate I/N101/130 code to indicate the organizations sending and receiving the transaction set.</i></b>	
		FR	Message From	
			<b><i>Use to indicate that the organization cited in N104 transmitted the transaction set.</i></b>	
		TO	Message To	
			<b><i>Use to indicate that the organization cited in N104 is to receive the transaction set.</i></b>	



**Segment:** **LM** Code Source Information  
**Position:** 200  
**Loop:** LM Optional  
**Level:** Heading  
**Usage:** Optional  
**Max Use:** 1  
**Purpose:** To transmit standard code list identification information  
**Syntax Notes:**  
**Semantic Notes:**  
**Comments:** 1 LM02 identifies the applicable industry code list source information.  
**Notes:** *Use this 1/LM/200 segment to identify coded information maintained in department or agency documentation when any specific LQ01 qualifier code applies to all line items. Use the 2/LM/185 segment when the LQ01 code varies by line item.*

#### Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	LM01	559	Agency Qualifier Code Code identifying the agency assigning the code values DF Department of Defense (DoD)	M ID 2/2
Not Used	LM02	822	Source Subqualifier A reference that indicates the table or text maintained by the Source Qualifier	O AN 1/15

**Segment:** **LQ** Industry Code  
**Position:** 210  
**Loop:** LM Optional  
**Level:** Heading  
**Usage:** Mandatory  
**Max Use:** 100  
**Purpose:** Code to transmit standard industry codes  
**Syntax Notes:** 1 If LQ01 is present, then LQ02 is required.  
**Semantic Notes:**  
**Comments:**  
**Notes:** *Use to identify codes, as appropriate, consistent with management information requirements.*

#### Data Element Summary

Ref.	Data		
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
LQ01	1270	Code List Qualifier Code	O ID 1/3
		Code identifying a specific industry code list	
		0 Document Identification Code	
		Codes that subclassify a transaction	
		10 Transaction Status Indicator Code	
		A transaction other than normal and therefore requiring special handling	
		<i>Use one of codes D - Interim Status, F - Final Reply Report or G - Ship To Code Differs From Contract, to indicate the transaction status.</i>	
		17 Shipment Acceptance Discrepancy Explanation Code	
		Either the reason for a difference between the quantity shipped and accepted, or why documentation is missing or incomplete	
		<i>Use to identify the shipment acceptance discrepancy explanation.</i>	
LQ02	1271	Industry Code	X AN 1/30
		Code indicating a code from a specific industry code list	

<b>Segment:</b>	<b>RCD</b> <b>Receiving Conditions</b>
<b>Position:</b>	010
<b>Loop:</b>	RCD Optional
<b>Level:</b>	Detail
<b>Usage:</b>	Optional
<b>Max Use:</b>	1
<b>Purpose:</b>	To report receiving conditions and specify contested quantities
<b>Syntax Notes:</b>	<ol style="list-style-type: none"> <li>1 At least one of RCD02 RCD04 or RCD06 is required.</li> <li>2 If either RCD02 or RCD03 is present, then the other is required.</li> <li>3 If either RCD04 or RCD05 is present, then the other is required.</li> <li>4 If any of RCD06 RCD07 or RCD08 is present, then all are required.</li> <li>5 If any of RCD09 RCD10 or RCD11 is present, then all are required.</li> <li>6 If any of RCD12 RCD13 or RCD14 is present, then all are required.</li> <li>7 If any of RCD15 RCD16 or RCD17 is present, then all are required.</li> <li>8 If any of RCD18 RCD19 or RCD20 is present, then all are required.</li> </ol>
<b>Semantic Notes:</b>	<ol style="list-style-type: none"> <li>1 RCD01 is the receiving advice line item identification.</li> <li>2 RCD21 is the cumulative quantity of goods received for a specific time period.</li> </ol>
<b>Comments:</b>	<ol style="list-style-type: none"> <li>1 See the Data Element Dictionary for a complete list of receiving condition IDs.</li> <li>2 RCD06 through RCD20 provide for five different quantities whose condition upon receipt is under question.</li> </ol>
<b>Notes:</b>	<i>Use the 2/RCD/010 loop to identify line item and acceptance information for a destination acceptance report.</i>

#### Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	RCD01	350	<b>Assigned Identification</b> Alphanumeric characters assigned for differentiation within a transaction set <i>Use to identify the Contract Line Item Number (CLIN), (including the Subcontract Line Item Number (SUBCLIN), Exhibit Line Item Number (ELIN), or Sub Exhibit Line Number Item (SUBELIN)).</i>	O AN 1/20
Must Use	RCD02	663	<b>Quantity Units Received or Accepted</b> Number of Units Received or Accepted <i>Use to identify only that quantity actually accepted at destination. Use the number 0 when transmitting an interim report.</i>	X R 1/9
Must Use	RCD03	C001	<b>Composite Unit of Measure</b> To identify a composite unit of measure (See Figures Appendix for examples of use)	X
M	C00101	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken <i>Use any code other than ZZ. DLMS users see the Unit of Issue and Purchase Unit Conversion Table for available codes.</i> Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 2/2

Not Used	C00102	1018	<b>Exponent</b> Power to which a unit is raised	O R 1/15
Not Used	C00103	649	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	O R 1/10
Not Used	C00104	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	O ID 2/2
Not Used	C00105	1018	<b>Exponent</b> Power to which a unit is raised	O R 1/15
Not Used	C00106	649	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	O R 1/10
Not Used	C00107	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	O ID 2/2
Not Used	C00108	1018	<b>Exponent</b> Power to which a unit is raised	O R 1/15
Not Used	C00109	649	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	O R 1/10
Not Used	C00110	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	O ID 2/2
Not Used	C00111	1018	<b>Exponent</b> Power to which a unit is raised	O R 1/15
Not Used	C00112	649	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	O R 1/10
Not Used	C00113	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	O ID 2/2
Not Used	C00114	1018	<b>Exponent</b> Power to which a unit is raised	O R 1/15
Not Used	C00115	649	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	O R 1/10
	RCD04	664	<b>Quantity Units Returned</b> Number of units returned	X R 1/9
	RCD05	C001	<b>Composite Unit of Measure</b> To identify a composite unit of measure (See Figures Appendix for examples of use)	X
M	C00101	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	M ID 2/2

*Use any code other than ZZ. DLMS users see the Unit of Issue and*

***Purchase Unit Conversion Table for available codes.***

Refer to 004010 Data Element Dictionary for acceptable code values.

Not Used	C00102	1018	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
Not Used	C00103	649	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
Not Used	C00104	355	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	C00105	1018	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
Not Used	C00106	649	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
Not Used	C00107	355	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	C00108	1018	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
Not Used	C00109	649	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
Not Used	C00110	355	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	C00111	1018	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
Not Used	C00112	649	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
Not Used	C00113	355	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	C00114	1018	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
Not Used	C00115	649	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
	RCD06	667	<b>Quantity in Question</b>	<b>X R 1/9</b>
			Number of units contested because of physical condition or status of units	
	RCD07	C001	<b>Composite Unit of Measure</b>	<b>X</b>
			To identify a composite unit of measure (See Figures Appendix for examples of use)	
M	C00101	355	<b>Unit or Basis for Measurement Code</b>	<b>M ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner	

in which a measurement has been taken

***Use any code other than ZZ. DLMS users see the Unit of Issue and Purchase Unit Conversion Table for available codes.***

Refer to 004010 Data Element Dictionary for acceptable code values.

Not Used	C00102	1018	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
Not Used	C00103	649	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
Not Used	C00104	355	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	C00105	1018	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
Not Used	C00106	649	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
Not Used	C00107	355	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	C00108	1018	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
Not Used	C00109	649	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
Not Used	C00110	355	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	C00111	1018	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
Not Used	C00112	649	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
Not Used	C00113	355	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	C00114	1018	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
Not Used	C00115	649	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
	RCD08	412	<b>Receiving Condition Code</b>	<b>X ID 2/2</b>
			Code designating physical condition or status of units received in a specific shipment	
			Refer to 004010 Data Element Dictionary for acceptable code values.	
	RCD09	667	<b>Quantity in Question</b>	<b>X R 1/9</b>

			Number of units contested because of physical condition or status of units	
	<b>RCD10</b>	<b>C001</b>	<b>Composite Unit of Measure</b>	<b>X</b>
			To identify a composite unit of measure (See Figures Appendix for examples of use)	
<b>M</b>	<b>C00101</b>	<b>355</b>	<b>Unit or Basis for Measurement Code</b>	<b>M ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
			<i>Use any code other than ZZ. DLMS users see the Unit of Issue and Purchase Unit Conversion Table for available codes.</i>	
			Refer to 004010 Data Element Dictionary for acceptable code values.	
<b>Not Used</b>	<b>C00102</b>	<b>1018</b>	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
<b>Not Used</b>	<b>C00103</b>	<b>649</b>	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
<b>Not Used</b>	<b>C00104</b>	<b>355</b>	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
<b>Not Used</b>	<b>C00105</b>	<b>1018</b>	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
<b>Not Used</b>	<b>C00106</b>	<b>649</b>	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
<b>Not Used</b>	<b>C00107</b>	<b>355</b>	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
<b>Not Used</b>	<b>C00108</b>	<b>1018</b>	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
<b>Not Used</b>	<b>C00109</b>	<b>649</b>	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
<b>Not Used</b>	<b>C00110</b>	<b>355</b>	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
<b>Not Used</b>	<b>C00111</b>	<b>1018</b>	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
<b>Not Used</b>	<b>C00112</b>	<b>649</b>	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
<b>Not Used</b>	<b>C00113</b>	<b>355</b>	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
<b>Not Used</b>	<b>C00114</b>	<b>1018</b>	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
<b>Not Used</b>	<b>C00115</b>	<b>649</b>	<b>Multiplier</b>	<b>O R 1/10</b>

			Value to be used as a multiplier to obtain a new value	
	<b>RCD11</b>	<b>412</b>	<b>Receiving Condition Code</b>	<b>X ID 2/2</b>
			Code designating physical condition or status of units received in a specific shipment	
			Refer to 004010 Data Element Dictionary for acceptable code values.	
	<b>RCD12</b>	<b>667</b>	<b>Quantity in Question</b>	<b>X R 1/9</b>
			Number of units contested because of physical condition or status of units	
	<b>RCD13</b>	<b>C001</b>	<b>Composite Unit of Measure</b>	<b>X</b>
			To identify a composite unit of measure (See Figures Appendix for examples of use)	
<b>M</b>	<b>C00101</b>	<b>355</b>	<b>Unit or Basis for Measurement Code</b>	<b>M ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
			<i>Use any code other than ZZ. DLMS users see the Unit of Issue and Purchase Unit Conversion Table for available codes.</i>	
			Refer to 004010 Data Element Dictionary for acceptable code values.	
<b>Not Used</b>	<b>C00102</b>	<b>1018</b>	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
<b>Not Used</b>	<b>C00103</b>	<b>649</b>	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
<b>Not Used</b>	<b>C00104</b>	<b>355</b>	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
<b>Not Used</b>	<b>C00105</b>	<b>1018</b>	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
<b>Not Used</b>	<b>C00106</b>	<b>649</b>	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
<b>Not Used</b>	<b>C00107</b>	<b>355</b>	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
<b>Not Used</b>	<b>C00108</b>	<b>1018</b>	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
<b>Not Used</b>	<b>C00109</b>	<b>649</b>	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
<b>Not Used</b>	<b>C00110</b>	<b>355</b>	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
<b>Not Used</b>	<b>C00111</b>	<b>1018</b>	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
<b>Not Used</b>	<b>C00112</b>	<b>649</b>	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	



Not Used	C00113	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	O ID 2/2
Not Used	C00114	1018	<b>Exponent</b> Power to which a unit is raised	O R 1/15
Not Used	C00115	649	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	O R 1/10
	RCD14	412	<b>Receiving Condition Code</b> Code designating physical condition or status of units received in a specific shipment Refer to 004010 Data Element Dictionary for acceptable code values.	X ID 2/2
	RCD15	667	<b>Quantity in Question</b> Number of units contested because of physical condition or status of units	X R 1/9
	RCD16	C001	<b>Composite Unit of Measure</b> To identify a composite unit of measure (See Figures Appendix for examples of use)	X
M	C00101	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken <i>Use any code other than ZZ. DLMS users see the Unit of Issue and Purchase Unit Conversion Table for available codes.</i> Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 2/2
Not Used	C00102	1018	<b>Exponent</b> Power to which a unit is raised	O R 1/15
Not Used	C00103	649	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	O R 1/10
Not Used	C00104	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	O ID 2/2
Not Used	C00105	1018	<b>Exponent</b> Power to which a unit is raised	O R 1/15
Not Used	C00106	649	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	O R 1/10
Not Used	C00107	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	O ID 2/2
Not Used	C00108	1018	<b>Exponent</b> Power to which a unit is raised	O R 1/15
Not Used	C00109	649	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	O R 1/10
Not Used	C00110	355	<b>Unit or Basis for Measurement Code</b>	O ID 2/2

			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	C00111	1018	<b>Exponent</b> Power to which a unit is raised	O R 1/15
Not Used	C00112	649	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	O R 1/10
Not Used	C00113	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	O ID 2/2
Not Used	C00114	1018	<b>Exponent</b> Power to which a unit is raised	O R 1/15
Not Used	C00115	649	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	O R 1/10
	RCD17	412	<b>Receiving Condition Code</b> Code designating physical condition or status of units received in a specific shipment Refer to 004010 Data Element Dictionary for acceptable code values.	X ID 2/2
	RCD18	667	<b>Quantity in Question</b> Number of units contested because of physical condition or status of units	X R 1/9
	RCD19	C001	<b>Composite Unit of Measure</b> To identify a composite unit of measure (See Figures Appendix for examples of use)	X
M	C00101	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken <i>Use any code other than ZZ. DLMS users see the Unit of Issue and Purchase Unit Conversion Table for available codes.</i> Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 2/2
Not Used	C00102	1018	<b>Exponent</b> Power to which a unit is raised	O R 1/15
Not Used	C00103	649	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	O R 1/10
Not Used	C00104	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	O ID 2/2
Not Used	C00105	1018	<b>Exponent</b> Power to which a unit is raised	O R 1/15
Not Used	C00106	649	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	O R 1/10
Not Used	C00107	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	O ID 2/2

<b>Not Used</b>	<b>C00108</b>	<b>1018</b>	<b>Exponent</b> Power to which a unit is raised	<b>O R 1/15</b>
<b>Not Used</b>	<b>C00109</b>	<b>649</b>	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	<b>O R 1/10</b>
<b>Not Used</b>	<b>C00110</b>	<b>355</b>	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	<b>O ID 2/2</b>
<b>Not Used</b>	<b>C00111</b>	<b>1018</b>	<b>Exponent</b> Power to which a unit is raised	<b>O R 1/15</b>
<b>Not Used</b>	<b>C00112</b>	<b>649</b>	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	<b>O R 1/10</b>
<b>Not Used</b>	<b>C00113</b>	<b>355</b>	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	<b>O ID 2/2</b>
<b>Not Used</b>	<b>C00114</b>	<b>1018</b>	<b>Exponent</b> Power to which a unit is raised	<b>O R 1/15</b>
<b>Not Used</b>	<b>C00115</b>	<b>649</b>	<b>Multiplier</b> Value to be used as a multiplier to obtain a new value	<b>O R 1/10</b>
	<b>RCD20</b>	<b>412</b>	<b>Receiving Condition Code</b> Code designating physical condition or status of units received in a specific shipment Refer to 004010 Data Element Dictionary for acceptable code values.	<b>X ID 2/2</b>
	<b>RCD21</b>	<b>380</b>	<b>Quantity</b> Numeric value of quantity	<b>O R 1/15</b>

<b>Segment:</b>	<b>SN1</b> Item Detail (Shipment)
<b>Position:</b>	020
<b>Loop:</b>	RCD Optional
<b>Level:</b>	Detail
<b>Usage:</b>	Optional
<b>Max Use:</b>	1
<b>Purpose:</b>	To specify line-item detail relative to shipment
<b>Syntax Notes:</b>	1 If either SN105 or SN106 is present, then the other is required.
<b>Semantic Notes:</b>	1 SN101 is the ship notice line-item identification.
<b>Comments:</b>	1 SN103 defines the unit of measurement for both SN102 and SN104.
<b>Notes:</b>	<i>Use to identify the material shipment quantity.</i>

## Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Not Used	SN101	350	<b>Assigned Identification</b> Alphanumeric characters assigned for differentiation within a transaction set	<b>O AN 1/20</b>
M	SN102	382	<b>Number of Units Shipped</b> Numeric value of units shipped in manufacturer's shipping units for a line item or transaction set <i>Use the 2/SN1/020 segment in 2/RCD/010 loops to identify the quantity shipped as indicated in the destination acceptance alert.</i>	<b>M R 1/10</b>
M	SN103	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken <i>Use to identify the purchase unit specified in the contract for the quantity shipped. Use any code other than code ZZ. DLMS users see the Unit of Issue and Purchase Unit Conversion Table for available codes.</i> Refer to 004010 Data Element Dictionary for acceptable code values.	<b>M ID 2/2</b>
Not Used	SN104	646	<b>Quantity Shipped to Date</b> Number of units shipped to date	<b>O R 1/15</b>
Not Used	SN105	330	<b>Quantity Ordered</b> Quantity ordered	<b>X R 1/15</b>
Not Used	SN106	355	<b>Unit or Basis for Measurement Code</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	<b>X ID 2/2</b>
Not Used	SN107	728	<b>Returnable Container Load Make-Up Code</b> Code identifying the load make-up of the returnable containers in the shipment	<b>O ID 1/2</b>
Not Used	SN108	668	<b>Line Item Status Code</b> Code specifying the action taken by the seller on a line item requested by	<b>O ID 2/2</b>

the buyer

<b>Segment:</b>	<b>REF</b> Reference Identification
<b>Position:</b>	070
<b>Loop:</b>	RCD Optional
<b>Level:</b>	Detail
<b>Usage:</b>	Optional
<b>Max Use:</b>	12
<b>Purpose:</b>	To specify identifying information
<b>Syntax Notes:</b>	<ol style="list-style-type: none"> <li>1 At least one of REF02 or REF03 is required.</li> <li>2 If either C04003 or C04004 is present, then the other is required.</li> <li>3 If either C04005 or C04006 is present, then the other is required.</li> </ol>
<b>Semantic Notes:</b>	<ol style="list-style-type: none"> <li>1 REF04 contains data relating to the value cited in REF02.</li> </ol>
<b>Comments:</b>	
<b>Notes:</b>	<i>Use this 2/REF/070 segment to identify reference numbers that apply to a specific line item. Use the 1/REF/050 segment to identify reference numbers that apply to all of the line items.</i>

Data Element Summary			
Ref.	Data		
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	REF01	128 Reference Identification Qualifier	M ID 2/3
		Code qualifying the Reference Identification	
		2U Payer Identification Number	
		55 Sequence Number	
		<i>Use, if applicable, to identify the suffix letter associated with a replacement shipment (e.g., when transmitting the letter A to indicate the first replacement shipment).</i>	
		AT Appropriation Number	
		<i>Use to indicate the long line of accounting. Cite the line of accounting in REF03.</i>	
		AX Government Accounting Class Reference Number (ACRN)	
		DD Document Identification Code	
		<i>Use to identify the document number.</i>	
		FS Final Sequence Number	
		<i>Use if applicable to identify the final shipment suffix Z.</i>	
		IL Internal Order Number	
		<i>Use to indicate a Communication Service Authorization (CSA) number.</i>	
		IX Item Number	
		P4 Project Code	
		<i>Use to identify the project center.</i>	

			RQ	Purchase Requisition No.	
			SI	Shipper's Identifying Number for Shipment (SID) A unique number (to the shipper) assigned by the shipper to identify the shipment <i>Use to identify the shipment number.</i>	
			TN	Transaction Reference Number <i>Use to identify the transaction number associated with the original requisition.</i>	
			VE	Vendor Abbreviation Code <i>Use to identify the source of supply.</i>	
			ZA	Supplier <i>Use to identify the supplier when the source of supply is other than prime vendor.</i>	
			ZZ	Mutually Defined <i>Use to indicate the Store Ownership Purpose Code.</i>	
Must Use	REF02	127	<b>Reference Identification</b>		X AN 1/30
			Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier		
	REF03	352	<b>Description</b>		X AN 1/80
			A free-form description to clarify the related data elements and their content		
	REF04	C040	<b>Reference Identifier</b>		O
			To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier		
M	C04001	128	<b>Reference Identification Qualifier</b>		M ID 2/3
			Code qualifying the Reference Identification		
			W8	Suffix Differentiates between partial actions taken on the original transaction <i>Use with REF01 code TN to identify the suffix code.</i>	
M	C04002	127	<b>Reference Identification</b>		M AN 1/30
			Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier		
Not Used	C04003	128	<b>Reference Identification Qualifier</b>		X ID 2/3
			Code qualifying the Reference Identification		
Not Used	C04004	127	<b>Reference Identification</b>		X AN 1/30
			Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier		
Not Used	C04005	128	<b>Reference Identification Qualifier</b>		X ID 2/3
			Code qualifying the Reference Identification		
Not Used	C04006	127	<b>Reference Identification</b>		X AN 1/30

Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier



**Segment: DTM Date/Time Reference****Position:** 090**Loop:** RCD Optional**Level:** Detail**Usage:** Optional**Max Use:** 10**Purpose:** To specify pertinent dates and times

- Syntax Notes:**
- 1 At least one of DTM02 DTM03 or DTM05 is required.
  - 2 If DTM04 is present, then DTM03 is required.
  - 3 If either DTM05 or DTM06 is present, then the other is required.

**Semantic Notes:****Comments:**

**Notes:** *Use this 2/DTM/090 segment to identify dates applicable to the line item. Use the 1/DTM/070 segment when the date applies to all of the line items.*

**Data Element Summary**

	<b>Ref.</b>	<b>Data</b>	<b>Name</b>	<b>Attributes</b>
	<b>Des.</b>	<b>Element</b>		
M	DTM01	374	<b>Date/Time Qualifier</b>	M ID 3/3
			Code specifying type of date or time, or both date and time	
			<i>Use only one code in any single 2/RCD/010 loop iteration.</i>	
		018	Available	
			<i>Use to indicate material was offered for delivery.</i>	
		035	Delivered	
			<i>Use to indicate material was delivered.</i>	
		050	Received	
		144	Estimated Acceptance	
			<i>Use to indicate material has an estimated acceptance date. Use in interim reports when LQ01 cites code 10 and LQ02 cites code D.</i>	
		201	Acceptance	
			<i>Use to indicate the material was accepted.</i>	
Must Use	DTM02	373	<b>Date</b>	X DT 8/8
			Date expressed as CCYYMMDD	
Not Used	DTM03	337	<b>Time</b>	X TM 4/8
			Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	
Not Used	DTM04	623	<b>Time Code</b>	O ID 2/2
			Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an	

indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow

<b>DTM05</b>	<b>1250</b>	<b>Date Time Period Format Qualifier</b>	<b>X ID 2/3</b>
		Code indicating the date format, time format, or date and time format	
		YY	Last Two Digits of Year Expressed in Format CCYY
			The year in the century (00 to 99)
			<i>Use in conjunction with DTM01 code 050 to indicate the FY obligated date.</i>
<b>DTM06</b>	<b>1251</b>	<b>Date Time Period</b>	<b>X AN 1/35</b>
		Expression of a date, a time, or range of dates, times or dates and times	
			<i>Enter the fiscal year in YY format.</i>

**Segment:** **PRF** Purchase Order Reference  
**Position:** 100  
**Loop:** RCD Optional  
**Level:** Detail  
**Usage:** Optional  
**Max Use:** 25  
**Purpose:** To provide reference to a specific purchase order  
**Syntax Notes:**  
**Semantic Notes:** 1 PRF04 is the date assigned by the purchaser to purchase order.  
**Comments:**

**Notes:** *Use this 2/PRF/100 segment to identify contract information applicable to the line item. Use the 1/PRF/080 segment when the contract information applies to all of the line items.*

#### Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	PRF01	324	<b>Purchase Order Number</b>	M AN 1/22
			Identifying number for Purchase Order assigned by the orderer/purchaser	
			<i>Enter the purchase order number, contract number (including Federal Supply Schedules, General Services Administration Schedules and all other basic contracts), Blanket Purchase Agreement number, Grant, Lease or Agreement number. This is always the Procurement Instrument identification Number for the Department of Defense or the equivalent expression for Civilian Agencies. This is never the number of a delivery order, call or release against a basic award instrument. That number is carried in PRF02. This number shall be transmitted without dashes.</i>	
	PRF02	328	<b>Release Number</b>	O AN 1/30
			Number identifying a release against a Purchase Order previously placed by the parties involved in the transaction	
			<i>Enter the number of a release, call or delivery order against a basic award instrument. This is always the Supplemental Procurement Instrument Identification Number for the Department of Defense or the equivalent expression for Civilian Agencies. This number shall be transmitted without dashes.</i>	
Not Used	PRF03	327	<b>Change Order Sequence Number</b>	O AN 1/8
			Number assigned by the orderer identifying a specific change or revision to a previously transmitted transaction set	
Not Used	PRF04	373	<b>Date</b>	O DT 8/8
			Date expressed as CCYYMMDD	
Not Used	PRF05	350	<b>Assigned Identification</b>	O AN 1/20
			Alphanumeric characters assigned for differentiation within a transaction set	

	<b>PRF06</b>	<b>367</b>	<b>Contract Number</b> Contract number <i>Use to identify the Small Business Administration (SBA) contract number for an 8a set-aside.</i>	<b>O AN 1/30</b>
<b>Not Used</b>	<b>PRF07</b>	<b>92</b>	<b>Purchase Order Type Code</b> Code specifying the type of Purchase Order	<b>O ID 2/2</b>

**Segment:** **LM** Code Source Information  
**Position:** 185  
**Loop:** LM Optional  
**Level:** Detail  
**Usage:** Optional  
**Max Use:** 1  
**Purpose:** To transmit standard code list identification information  
**Syntax Notes:**  
**Semantic Notes:**  
**Comments:** 1 LM02 identifies the applicable industry code list source information.  
**Notes:**

*Use this 2/LM/185 segment to identify coded information maintained in department or agency documentation when any specific LQ01 qualifier code applies to the line item. Use the 1/LM/200 segment when the LQ01 code applies to all line items.*

#### Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	LM01	559	Agency Qualifier Code Code identifying the agency assigning the code values DF Department of Defense (DoD)	M ID 2/2
Not Used	LM02	822	Source Subqualifier A reference that indicates the table or text maintained by the Source Qualifier	O AN 1/15

<b>Segment:</b>	<b>LQ</b> Industry Code
<b>Position:</b>	186
<b>Loop:</b>	LM Optional
<b>Level:</b>	Detail
<b>Usage:</b>	Mandatory
<b>Max Use:</b>	100
<b>Purpose:</b>	Code to transmit standard industry codes
<b>Syntax Notes:</b>	1 If LQ01 is present, then LQ02 is required.
<b>Semantic Notes:</b>	
<b>Comments:</b>	
<b>Notes:</b>	<i>Use to identify codes, as appropriate, consistent with management information requirements.</i>

#### Data Element Summary

<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
<u>Des.</u>	<u>Element</u>		
<b>LQ01</b>	<b>1270</b>	<b>Code List Qualifier Code</b>	<b>O ID 1/3</b>
		Code identifying a specific industry code list	
		0 Document Identification Code	
		Codes that subclassify a transaction	
		10 Transaction Status Indicator Code	
		A transaction other than normal and therefore requiring special handling	
		<i>Use one of codes D - Interim Status, F - Final Reply Report or G - Ship To Code Differs From Contract, to indicate the transaction status.</i>	
		17 Shipment Acceptance Discrepancy Explanation Code	
		Either the reason for a difference between the quantity shipped and accepted, or why documentation is missing or incomplete	
		<i>Use to identify the shipment acceptance discrepancy explanation.</i>	
<b>LQ02</b>	<b>1271</b>	<b>Industry Code</b>	<b>X AN 1/30</b>
		Code indicating a code from a specific industry code list	

<b>Segment:</b>	<b>SLN</b> Subline Item Detail
<b>Position:</b>	190
<b>Loop:</b>	SLN Optional
<b>Level:</b>	Detail
<b>Usage:</b>	Optional
<b>Max Use:</b>	1
<b>Purpose:</b>	To specify product subline detail item data
<b>Syntax Notes:</b>	<ol style="list-style-type: none"> <li>1 If either SLN04 or SLN05 is present, then the other is required.</li> <li>2 If SLN07 is present, then SLN06 is required.</li> <li>3 If SLN08 is present, then SLN06 is required.</li> <li>4 If either SLN09 or SLN10 is present, then the other is required.</li> <li>5 If either SLN11 or SLN12 is present, then the other is required.</li> <li>6 If either SLN13 or SLN14 is present, then the other is required.</li> <li>7 If either SLN15 or SLN16 is present, then the other is required.</li> <li>8 If either SLN17 or SLN18 is present, then the other is required.</li> <li>9 If either SLN19 or SLN20 is present, then the other is required.</li> <li>10 If either SLN21 or SLN22 is present, then the other is required.</li> <li>11 If either SLN23 or SLN24 is present, then the other is required.</li> <li>12 If either SLN25 or SLN26 is present, then the other is required.</li> <li>13 If either SLN27 or SLN28 is present, then the other is required.</li> </ol>
<b>Semantic Notes:</b>	<ol style="list-style-type: none"> <li>1 SLN01 is the identifying number for the subline item.</li> <li>2 SLN02 is the identifying number for the subline level. The subline level is analogous to the level code used in a bill of materials.</li> <li>3 SLN03 is the configuration code indicating the relationship of the subline item to the baseline item.</li> <li>4 SLN08 is a code indicating the relationship of the price or amount to the associated segment.</li> </ol>
<b>Comments:</b>	<ol style="list-style-type: none"> <li>1 See the Data Element Dictionary for a complete list of IDs.</li> <li>2 SLN01 is related to (but not necessarily equivalent to) the baseline item number. Example: 1.1 or 1A might be used as a subline number to relate to baseline number 1.</li> <li>3 SLN09 through SLN28 provide for ten different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.</li> </ol>
<b>Notes:</b>	<i>Use this segment to identify components missing from a shipment.</i>

#### Data Element Summary

Ref.	Data		
Des.	Element	Name	Attributes
M	SLN01	350 Assigned Identification	M AN 1/20
		Alphanumeric characters assigned for differentiation within a transaction set	
		<i>Use as a counter. Start with the number 1 and increase the number by 1 for each iteration of the segment.</i>	
	SLN02	350 Assigned Identification	O AN 1/20
		Alphanumeric characters assigned for differentiation within a transaction	

			set	
			<i>Use to indicate, as applicable, the associated line item.</i>	
<b>M</b>	<b>SLN03</b>	<b>662</b>	<b>Relationship Code</b>	<b>M ID 1/1</b>
			Code indicating the relationship between entities	
			A	Add
			D	Delete
			I	Included
			O	Information Only
				Charges which relate to but may not be included in or added to the unit price of the SLN. (i.e., compute WATS calculation based upon usage amounts)
			S	Substituted
<b>Must Use</b>	<b>SLN04</b>	<b>380</b>	<b>Quantity</b>	<b>X R 1/15</b>
			Numeric value of quantity	
			<i>Use to identify the missing quantity.</i>	
<b>Must Use</b>	<b>SLN05</b>	<b>C001</b>	<b>Composite Unit of Measure</b>	<b>X</b>
			To identify a composite unit of measure (See Figures Appendix for examples of use)	
<b>M</b>	<b>C00101</b>	<b>355</b>	<b>Unit or Basis for Measurement Code</b>	<b>M ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
			<i>Use any code other than ZZ. DLMS users see the Unit of Issue and Purchase Unit Conversion Table for available codes. The cited code should be the same code used in the 856 Shipment Notice that applies to the missing component.</i>	
			Refer to 004010 Data Element Dictionary for acceptable code values.	
<b>Not Used</b>	<b>C00102</b>	<b>1018</b>	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
<b>Not Used</b>	<b>C00103</b>	<b>649</b>	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
<b>Not Used</b>	<b>C00104</b>	<b>355</b>	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
<b>Not Used</b>	<b>C00105</b>	<b>1018</b>	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	
<b>Not Used</b>	<b>C00106</b>	<b>649</b>	<b>Multiplier</b>	<b>O R 1/10</b>
			Value to be used as a multiplier to obtain a new value	
<b>Not Used</b>	<b>C00107</b>	<b>355</b>	<b>Unit or Basis for Measurement Code</b>	<b>O ID 2/2</b>
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
<b>Not Used</b>	<b>C00108</b>	<b>1018</b>	<b>Exponent</b>	<b>O R 1/15</b>
			Power to which a unit is raised	



Not Used	C00109	649	<b>Multiplier</b>	O R 1/10
			Value to be used as a multiplier to obtain a new value	
Not Used	C00110	355	<b>Unit or Basis for Measurement Code</b>	O ID 2/2
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	C00111	1018	<b>Exponent</b>	O R 1/15
			Power to which a unit is raised	
Not Used	C00112	649	<b>Multiplier</b>	O R 1/10
			Value to be used as a multiplier to obtain a new value	
Not Used	C00113	355	<b>Unit or Basis for Measurement Code</b>	O ID 2/2
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	C00114	1018	<b>Exponent</b>	O R 1/15
			Power to which a unit is raised	
Not Used	C00115	649	<b>Multiplier</b>	O R 1/10
			Value to be used as a multiplier to obtain a new value	
	SLN06	212	<b>Unit Price</b>	X R 1/17
			Price per unit of product, service, commodity, etc.	
			<i>Use to indicate the unit price applicable to the missing component. When SLN07 is a code that has no associated price, e.g., code NC, NS, TB, etc., cite a "0" in this data element.</i>	
	SLN07	639	<b>Basis of Unit Price Code</b>	O ID 2/2
			Code identifying the type of unit price for an item	
			<i>Use any code.</i>	
			Refer to 004010 Data Element Dictionary for acceptable code values.	
	SLN08	662	<b>Relationship Code</b>	O ID 1/1
			Code indicating the relationship between entities	
			A Add	
			D Delete	
			I Included	
			O Information Only	
			Charges which relate to but may not be included in or added to the unit price of the SLN. (i.e., compute WATS calculation based upon usage amounts)	
			S Substituted	
	SLN09	235	<b>Product/Service ID Qualifier</b>	X ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
			<i>Use any code other than code ZZ. The cited code should be the same code used in the 856 Shipment Notice that applies to the missing component.</i>	
			Refer to 004010 Data Element Dictionary for acceptable code values.	

<b>SLN10</b>	<b>234</b>	<b>Product/Service ID</b>	<b>X AN 1/48</b>
		Identifying number for a product or service	
<b>SLN11</b>	<b>235</b>	<b>Product/Service ID Qualifier</b>	<b>X ID 2/2</b>
		Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
		Refer to 004010 Data Element Dictionary for acceptable code values.	
<b>SLN12</b>	<b>234</b>	<b>Product/Service ID</b>	<b>X AN 1/48</b>
		Identifying number for a product or service	
<b>SLN13</b>	<b>235</b>	<b>Product/Service ID Qualifier</b>	<b>X ID 2/2</b>
		Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
		Refer to 004010 Data Element Dictionary for acceptable code values.	
<b>SLN14</b>	<b>234</b>	<b>Product/Service ID</b>	<b>X AN 1/48</b>
		Identifying number for a product or service	
<b>SLN15</b>	<b>235</b>	<b>Product/Service ID Qualifier</b>	<b>X ID 2/2</b>
		Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
		Refer to 004010 Data Element Dictionary for acceptable code values.	
<b>SLN16</b>	<b>234</b>	<b>Product/Service ID</b>	<b>X AN 1/48</b>
		Identifying number for a product or service	
<b>SLN17</b>	<b>235</b>	<b>Product/Service ID Qualifier</b>	<b>X ID 2/2</b>
		Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
		Refer to 004010 Data Element Dictionary for acceptable code values.	
<b>SLN18</b>	<b>234</b>	<b>Product/Service ID</b>	<b>X AN 1/48</b>
		Identifying number for a product or service	
<b>SLN19</b>	<b>235</b>	<b>Product/Service ID Qualifier</b>	<b>X ID 2/2</b>
		Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
		Refer to 004010 Data Element Dictionary for acceptable code values.	
<b>SLN20</b>	<b>234</b>	<b>Product/Service ID</b>	<b>X AN 1/48</b>
		Identifying number for a product or service	
<b>SLN21</b>	<b>235</b>	<b>Product/Service ID Qualifier</b>	<b>X ID 2/2</b>
		Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
		Refer to 004010 Data Element Dictionary for acceptable code values.	
<b>SLN22</b>	<b>234</b>	<b>Product/Service ID</b>	<b>X AN 1/48</b>
		Identifying number for a product or service	
<b>SLN23</b>	<b>235</b>	<b>Product/Service ID Qualifier</b>	<b>X ID 2/2</b>
		Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
		Refer to 004010 Data Element Dictionary for acceptable code values.	

<b>SLN24</b>	<b>234</b>	<b>Product/Service ID</b>	<b>X AN 1/48</b>
		Identifying number for a product or service	
<b>SLN25</b>	<b>235</b>	<b>Product/Service ID Qualifier</b>	<b>X ID 2/2</b>
		Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
		Refer to 004010 Data Element Dictionary for acceptable code values.	
<b>SLN26</b>	<b>234</b>	<b>Product/Service ID</b>	<b>X AN 1/48</b>
		Identifying number for a product or service	
<b>SLN27</b>	<b>235</b>	<b>Product/Service ID Qualifier</b>	<b>X ID 2/2</b>
		Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
		Refer to 004010 Data Element Dictionary for acceptable code values.	
<b>SLN28</b>	<b>234</b>	<b>Product/Service ID</b>	<b>X AN 1/48</b>
		Identifying number for a product or service	

<b>Segment:</b>	<b>PID</b> <b>Product/Item Description</b>
<b>Position:</b>	200
<b>Loop:</b>	SLN      Optional
<b>Level:</b>	Detail
<b>Usage:</b>	Optional
<b>Max Use:</b>	1000
<b>Purpose:</b>	To describe a product or process in coded or free-form format
<b>Syntax Notes:</b>	<ol style="list-style-type: none"> <li>1 If PID04 is present, then PID03 is required.</li> <li>2 At least one of PID04 or PID05 is required.</li> <li>3 If PID07 is present, then PID03 is required.</li> <li>4 If PID08 is present, then PID04 is required.</li> <li>5 If PID09 is present, then PID05 is required.</li> </ol>
<b>Semantic Notes:</b>	<ol style="list-style-type: none"> <li>1 Use PID03 to indicate the organization that publishes the code list being referred to.</li> <li>2 PID04 should be used for industry-specific product description codes.</li> <li>3 PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.</li> <li>4 PID09 is used to identify the language being used in PID05.</li> </ol>
<b>Comments:</b>	<ol style="list-style-type: none"> <li>1 If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.</li> <li>2 Use PID06 when necessary to refer to the product surface or layer being described in the segment.</li> <li>3 PID07 specifies the individual code list of the agency specified in PID03.</li> </ol>
<b>Notes:</b>	<i>Use this segment when it is necessary to further describe a component missing from a shipment.</i>

#### Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	PID01	349	Item Description Type Code indicating the format of a description F                      Free-form	M ID 1/1
Not Used	PID02	750	Product/Process Characteristic Code Code identifying the general class of a product or process characteristic	O ID 2/3
Not Used	PID03	559	Agency Qualifier Code Code identifying the agency assigning the code values	X ID 2/2
Not Used	PID04	751	Product Description Code A code from an industry code list which provides specific data about a product characteristic	X AN 1/12
Must Use	PID05	352	Description A free-form description to clarify the related data elements and their content <i>Use to describe the item cited in SLN02 only when an additional description is required.</i>	X AN 1/80

<b>Not Used</b>	<b>PID06</b>	<b>752</b>	<b>Surface/Layer/Position Code</b> Code indicating the product surface, layer or position that is being described	<b>O ID 2/2</b>
<b>Not Used</b>	<b>PID07</b>	<b>822</b>	<b>Source Subqualifier</b> A reference that indicates the table or text maintained by the Source Qualifier	<b>O AN 1/15</b>
<b>Not Used</b>	<b>PID08</b>	<b>1073</b>	<b>Yes/No Condition or Response Code</b> Code indicating a Yes or No condition or response	<b>O ID 1/1</b>
<b>Not Used</b>	<b>PID09</b>	<b>819</b>	<b>Language Code</b> Code designating the language used in text, from a standard code list maintained by the International Standards Organization (ISO 639)	<b>O ID 2/3</b>

**Segment:** **LM** Code Source Information  
**Position:** 205  
**Loop:** LM Optional  
**Level:** Detail  
**Usage:** Optional  
**Max Use:** 1  
**Purpose:** To transmit standard code list identification information  
**Syntax Notes:**  
**Semantic Notes:**  
**Comments:** 1 LM02 identifies the applicable industry code list source information.  
**Notes:** *Use this loop to provide additional information from a Department of Defense code list that applies to the missing component.*

#### Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	LM01	559	Agency Qualifier Code Code identifying the agency assigning the code values DF Department of Defense (DoD)	M ID 2/2
Not Used	LM02	822	Source Subqualifier A reference that indicates the table or text maintained by the Source Qualifier	O AN 1/15

**Segment:** **LQ** Industry Code  
**Position:** 206  
**Loop:** LM Optional  
**Level:** Detail  
**Usage:** Mandatory  
**Max Use:** 100  
**Purpose:** Code to transmit standard industry codes  
**Syntax Notes:** 1 If LQ01 is present, then LQ02 is required.  
**Semantic Notes:**  
**Comments:**

Notes: *Use this segment to provide codes consistent with information related to the missing component.*

#### Data Element Summary

Ref.	Data		
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
LQ01	1270	Code List Qualifier Code	O ID 1/3
		Code identifying a specific industry code list	
		10 Transaction Status Indicator Code	
		A transaction other than normal and therefore requiring special handling	
		17 Shipment Acceptance Discrepancy Explanation Code	
		Either the reason for a difference between the quantity shipped and accepted, or why documentation is missing or incomplete	
LQ02	1271	Industry Code	X AN 1/30
		Code indicating a code from a specific industry code list	

**Segment:** **SE** Transaction Set Trailer  
**Position:** 020  
**Loop:**  
**Level:** Summary  
**Usage:** Mandatory  
**Max Use:** 1  
**Purpose:** To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)  
**Syntax Notes:**  
**Semantic Notes:**  
**Comments:** 1 SE is the last segment of each transaction set.

#### Data Element Summary

	Ref.	Data		
	<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	SE01	96	Number of Included Segments	M N0 1/10
			Total number of segments included in a transaction set including ST and SE segments	
M	SE02	329	Transaction Set Control Number	M AN 4/9
			Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	
			<i>Cite the same number as the one cited in ST02.</i>	